



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	XS, S, M, L, XL
COLORIS	Black/Blue
CADRE	ALUXX SL-grade aluminum, Advanced forged composite upper rocker, 140mm Maestro suspension system
FOURCHE	Fox 36 Float Rhythm 27.5+ 150mm, EVOL, Grip Damper, Sweep adjust, Boost 110x15QR, e-Bike optimized
AMORTISSEUR	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position lever, 185x52.5mm Trunnion mount, custom tuned
COMPOSANTS	
CINTRE	Giant Contact 35 Trail, 35x800mm
POTENCE	Giant Contact SL 35
TIGE DE SELLE	Giant Contact Switch, dropper, 30,9mm, under bar remote lever
SELLE	Giant Contact, Neutral
DÉRAILLEUR	
MANETTES	Shimano SLX
DÉRAILLEUR AVANT	MRP 1X CS custom
DÉRAILLEUR ARRIÈRE	Shimano Deore XT, 11-Speed, Shadow+
FREINS	Shimano BR-MT520, 4-piston, hydraulic disc, 203mm
LEVIERS DE FREIN	Shimano BL-MT520, i-spec II
CASSETTE	Shimano HG-M7000, 11-46T, 11-Speed
CHAÎNE	KMC e.11 Turbo, EcoProteq, e-bike optimized
PÉDALIER	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set
ROUES	
JANTES	Giant AM 27.5+, Tubeless ready, 35mm inner width, e-bike optimized
MOYEURS	Giant eTracker Boost, Sealed cartridge bearing, 6-bolt, [F] 110x15 [R] 148x12mm Thru-axle, e-bike optimized
RAYONS	Sapim E-Lite [r] Race [f], e-bike optimized
PNEUS	Maxxis Minion DHF 27.5x2.6" Foldable, Tubeless, EXO, Dual compound [F] Maxxis Rekon 27.5x2.6" Foldable, Tubeless, EXO, Dual Compound [R]
EXTRAS	Giant EnergyPak 6A Smart charger (60% charge in 60minutes) Tubeless kit
TECHNOLOGIE HYBRID	
MOTEUR	Giant SyncDrive Pro, 360% tuneable support, powered by YAMAHA
CAPTEURS	Giant PedalPlus 4-sensor technology
CONSOLE	Giant RideControl ONE, remote button
BATTERIE	Giant EnergyPak 500, 36V 13.8Ah integrated Lithium-Ion

CARACTÉRISTIQUES

- Giant SyncDrive Pro, 360% tuneable support, powered by YAMAHA
- Giant EnergyPak500 lithium-ion battery
- Fox 36 Rhythm 150mm travel suspension fork
- Shimano XT / SLX 11-speed Drivetrain
- Shimano 4-piston hydraulic brakes
- Remote height adjust seatpost

Prix: 4 399 €

GÉOMÉTRIE

CADRE	XS	S	M	L	XL
Longueur de tube de selle (mm)	380	406	445	482	507
Angle de tube de selle	74,0°	74,0°	74,0°	74,0°	74,0°
Longueur du tube supérieur (mm)	570	585	610	630	655
Longueur du tube de direction (mm)	95	95	100	110	130
Angle du tube de direction	66,5°	66,5°	66,5°	66,5°	66,5°
Déport de fourche (mm)	46	46	46	46	46
Trail (mm)	109	109	109	109	109
Empattement (mm)	1169	1184	1210	1231	1259
Longueur fourche de pédalier (mm)	470	470	470	470	470
Hauteur du boîtier de pédalier (mm)	15	15	15	15	15
Stack (mm)	579	579	584	593	611
Reach (mm)	403	418	442	460	479
Hauteur en statique (mm)	728	739	740	772	792
Largeur de cintre (mm)	780	780	780	780	780
Longueur de potence (mm)	40	40	50	50	60
Longueur des manivelles (mm)	165	165	170	170	170
Diamètre des roues	27.5+	27.5+	27.5+	27.5+	27.5+

Produits conformes aux exigences de sécurité (décret n°95-937). GIANT France se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.